

VIBGYOR SPRAY TEX is a premixed pigmented decorative thick textured wall finish. It is composed of Acrylic Polymers/ Resins, quartz powders, marble chips, natural aggregates and has a drop effect. The thickness of Spray Tex varies from 1.4- 2 mm and it hides minor cracks imperfection of plaster, uneven patches and can be applied in bubble and compact both in single or multi shades. It is good for Exterior and Interior and is available in a variety of colours.

Features

- SINGLE COAT APPLICATION.
- SUITABLE FOR EXTERIOR / INTERIOR.
- LONGEST SHADE LIFE.
- UNIQUE FLEXIBILITY AND ELASTICITY.
- BREATHES OUT TRAPPED MOISTURE.
- ECONOMICAL AND TIME EFFECTIVE.
- WATER REPELLENT.
- ANTI FUNGUS.

Technical Characteristics

SPRAY TEX is a thick wall coating that is highly resistant to alkalies and wear and tear. Copolymer adhesive powers make them ideal for virtually any kind of substrate.

Use

SPRAY TEX may be used for the decoration and protection of External and Internal cement plaster, gypsum or concrete surface. It is suitable for housing societies, apartments and commercial complexes.

Application

SPRAY TEX should be applied onto the surface two coats with brush and followed by Spray Gun specially designed for this kind of application. To get compact effect, plastic trowel to be applied in semi dry condition. The material is rainproof after 8 hours of application and hardens completely within 48 hours, at a temperature of 20oC.

SURFACE PREPARATION

New, smooth and regular plasters do not need any special preparation. Old, flaking, P.O.P, Gypsum surfaces or very absorbent plasters should be first brushed down and then treated with a coat of VIBGYOR Sealer, mixed with water in the ratio 1 : 3 (sealer one part, water three parts) and applied by a brush. Broken edges, undulations, loose and flaky surfaces can be rectified by using a paste made of VIBGYOR CONCREBOND - 250 surface improver mixed with ordinary Portland Cement in the ratio 1 : 1 with silica sand.

CONSUMPTION

To cover one sq.mtr. area 2.75 to 3.00 Kg. of SPRAY TEX.

PACKING

SPRAY TEX is available in ready-to-use form in 35 Kgs. Containers.

IMPORTANT

- Preserve the product from excessive heat and cold.
- Mix the product well before use.
- Wash all equipment with water immediately after use.
- To cover large surface areas it is advisable to divide the surface into panels in order to avoid irregular joints.
- Avoid application in hot sun and strong winds.

Application has to be carried out a temperature, above 5oC.

